

# EventMgr Objects

## Introduction

An **EventMgr** object manages the collection and distribution of event messages from the controller to the host. Events include normal motion completion, motor limits, fault conditions, data recorder buffer full, network node faults, etc. The EventNotify methods enable the application to request host notification for specified events, while ignoring other events. The EventMgr receives the event and then distributes the event via the Notify object to the tasks that are waiting for the event. Events that are faults are latched; the fault condition and the event must be cleared before the event can be generated again.

To collect events, the EventMgr must be serviced via the [mpiEventMgrService\(...\)](#) routine. The EventMgr can be polled by periodically by calling the mpiEventMgrService(...) routine or can be placed in an interrupt service routine. For your convenience, there is an apputil module that provides a serviceCreate(...) function that creates an EventMgr service routine for Windows OSs. The Service thread can be configured for polling or interrupts. Sources for the apputil module are included with the software distribution, so you can port it to other OSs.

The controller has a circular buffer which holds up to 128 event messages. If the EventMgr is not serviced within 128 events, event messages will be overwritten as new events occur. For interrupt driven EventMgr service threads, this is not an issue. For a polling EventMgr service thread, this could be an issue if the service thread does not have enough CPU cycles. In the worst-case scenario, events could be lost.

The best way to avoid lost events is to use an interrupt driven EventMgr service routine. If you're using polling, the next best thing is to make sure the EventMgr services the events at a high enough rate to avoid controller message buffer rollover. Determining the worst case EventMgr service latency and the maximum event message rate can be tricky. A simple method is to estimate the event message frequency and make sure each EventMgr can poll at least once for every 32 events (safety factor of 4). If you know that some events occur more frequently than others, then you may want to increase the polling frequency for EventMgrs that process the most frequent events and decrease the polling frequency for EventMgrs that process less frequently.

Generally, use only one EventMgr in your application. Do not use multiple interrupt driven EventMgr service threads to collect the same event. Suppose you configure an EventMgr to service Motion Done events from MS 0 and you configure another EventMgr with MEIEventMgrServiceConfig.allProcesses = TRUE. If one EventMgr collects the event message and acknowledges the interrupt before the other EventMgr can respond, it will miss the event.

If you want to monitor ALL events with MEIEventMgrServiceConfig.allProcesses = TRUE, then use polling (not interrupts). See the sample app EventLog.c for an example.

### WARNING

Resetting the motion controller will cause any existing EventMgr objects to become unsynchronized with the motion controller, causing it to miss events. It is recommended that after a controller reset, an application should delete and re-create the EventMgr and Service objects. Then the application should reconnect all Notify objects to the EventMgr and re-enable event reporting by calling **ObjectEventNotifySet**.

## Methods

### Create, Delete, Validate Methods

<a href="#">mpiEventMgrCreate</a>	Create EventMgr object
<a href="#">mpiEventMgrDelete</a>	Delete EventMgr object
<a href="#">mpiEventMgrValidate</a>	Validate EventMgr object

### Configuration and Information Methods

<a href="#">mpiEventMgrConfigGet</a>	Get EventMgr config
<a href="#">mpiEventMgrConfigSet</a>	Set EventMgr config
<a href="#">mpiEventMgrEvent</a>	Request event notification for all Notify objects on EventMgr's list
<a href="#">meiEventMgrServiceConfigGet</a>	Get processes that EventMgr will service
<a href="#">meiEventMgrServiceConfigSet</a>	Set processes that EventMgr will service

### Action Methods

<a href="#">mpiEventMgrFlush</a>	Flush pending EventMgr events
<a href="#">mpiEventMgrService</a>	Get list of all pending asynchronous events

### Relational Methods

#### List Methods- for Control Objects

<a href="#">mpiEventMgrControl</a>	Return handle of indexth Control object in list
<a href="#">mpiEventMgrControlAppend</a>	Append Control's handle to list
<a href="#">mpiEventMgrControlCount</a>	Count the number of Control objects associated with EventMgr (in list)
<a href="#">mpiEventMgrControlFirst</a>	Return handle to first Control object in list
<a href="#">mpiEventMgrControlIndex</a>	Return the index of a Control object in list
<a href="#">mpiEventMgrControlInsert</a>	Insert Control handle into list
<a href="#">mpiEventMgrControlLast</a>	Get handle to last Control object in list
<a href="#">mpiEventMgrControlListGet</a>	Get list of Control objects associated with EventMgr
<a href="#">mpiEventMgrControlListSet</a>	Create a list of Control objects associated with EventMgr
<a href="#">mpiEventMgrControlNext</a>	Get handle to next Control object in list
<a href="#">mpiEventMgrControlPrevious</a>	Get handle to previous Control object in list
<a href="#">mpiEventMgrControlRemove</a>	Remove a Control object's handle from list

#### List Methods- for Notify Objects

<a href="#">mpiEventMgrNotify</a>	Return handle to a Notify object associated with EventMgr
<a href="#">mpiEventMgrNotifyAppend</a>	Append Notify object to list
<a href="#">mpiEventMgrNotifyCount</a>	Return number of Notify objects in list
<a href="#">mpiEventMgrNotifyFirst</a>	Get first Notify object in list
<a href="#">mpiEventMgrNotifyIndex</a>	Get index value for a Notify object in list

[mpiEventMgrNotifyInsert](#)  
[mpiEventMgrNotifyLast](#)  
[mpiEventMgrNotifyListGet](#)  
[mpiEventMgrNotifyListSet](#)  
[mpiEventMgrNotifyNext](#)  
[mpiEventMgrNotifyPrevious](#)  
[mpiEventMgrNotifyRemove](#)

Place a Notify object after another Notify object in list  
Get handle to the Notify object that is last on the list  
Get a list of Notify objects  
Create a list of Notify objects  
Get the Notify object just after notify in list  
Get the Notify object just before notify in list  
Remove a Notify object from list

## Data Types

[MPIEventMgrConfig](#)  
[MPIEventMgrMessage](#)  
[MEIEventMgrServiceConfig](#)

# mpiEventMgrService

## Declaration

```
long mpiEventMgrService(MPIEventMgr eventMgr ,
                        MPIControl control )
```

**Required Header:** stdmpi.h

## Description

**mpiEventMgrService** obtains all pending asynchronous events from the motion controller (**control**).

Events generated by enabled sources are returned in First-In/First-Out (FIFO) order each time a thread calls mpiEventMgrService(...).

Typically, after a motion controller generates a hardware interrupt, the Interrupt Service Routine (ISR) is invoked, and the ISR in turn invokes mpiEventMgrService(...) directly or indirectly.

<i>If "control" is</i>	<b>Then</b>
MPIHandleVOID	events will be obtained from all motion controllers on the EventMgr's ( <b>eventMgr</b> ) control list
valid	<b>control</b> must also be present on the EventMgr's ( <b>eventMgr</b> ) control list

## Return Values

[MPIMessageOK](#)

## See Also

[meiEventMgrServiceConfigGet](#) | [meiEventMgrServiceConfigSet](#) | [mpiEventMgrFlush](#)

# mpiEventMgrCreate

## Declaration

```
MPIEventMgr mpiEventMgrCreate(MPIControl control)
```

Required Header: stdmpi.h

## Description

**mpiEventMgrCreate** creates an EventMgr object, with **control** as the initial element in the list of Control objects from which the EventMgr obtains asynchronous events (**control** may be MPIHandleVOID).

EventMgrCreate is the equivalent of a C++ constructor.

### Return Values

<b>handle</b>	to an EventMgr object
<b>MPIHandleVOID</b>	if the object could not be created

## See Also

[mpiEventMgrDelete](#) | [mpiEventMgrValidate](#)

# mpiEventMgrDelete

## Declaration

```
long mpiEventMgrDelete(MPIEventMgr eventMgr )
```

**Required Header:** stdmpi.h

## Description

**mpiEventMgrDelete** deletes an EventMgr object and invalidates its handle (*eventMgr*). EventMgrDelete is the equivalent of a C++ destructor.

Deleting an EventMgr object does not delete any of the Control objects that supply the EventMgr with asynchronous events. However, deleting an EventMgr object will delete any unreceived events for that EventMgr.

## Return Values

[MPIMessageOK](#)

## See Also

[mpiEventMgrCreate](#) | [mpiEventMgrValidate](#)

# mpiEventMgrValidate

## Declaration

```
long mpiEventMgrValidate(MPIEventMgr eventMgr )
```

Required Header: stdmpi.h

## Description

**mpiEventMgrValidate** validates an EventMgr object and its handle (*eventMgr*).

## Return Values

[MPIMessageOK](#)

## See Also

[mpiEventMgrCreate](#) | [mpiEventMgrDelete](#)

# mpiEventMgrConfigGet

## Declaration

```
long mpiEventMgrConfigGet (MPIEventMgr      eventMgr ,
                           MPIEventMgrConfig *config ,
                           void             *external )
```

Required Header: stdmpi.h

## Description

**mpiEventMgrConfigGet** gets the configuration of an *EventMgr* object (eventMgr) and writes it into the structure pointed to by *config*, and also writes it into the implementation-specific structure pointed to by *external* (if *external* is not NULL).

The configuration information in *external* is in addition to the configuration information in *config*, i.e., the configuration information in *config* and in *external* is not the same information. Note that *config* or *external* can be NULL (but not both NULL).

## Remarks

*external* either points to a structure of type **MEIEventMgrConfig{}** or is NULL.

### Return Values

[MPIMessageOK](#)

## See Also

[mpiEventMgrConfigSet](#)



# mpiEventMgrConfigSet

## Declaration

```
long mpiEventMgrConfigSet( MPIEventMgr      eventMgr ,
                           MPIEventMgrConfig *config ,
                           void                *external )
```

Required Header: stdmpi.h

## Description

**mpiEventMgrConfigSet** sets (writes) the *eventMgr* configuration using data from the structure pointed to by *config*, and also using data from the implementation-specific structure pointed to by *external* (if *external* is not NULL).

The configuration information in *external* is in addition to the configuration information in *config*, i.e., the configuration information in *config* and in *external* is not the same information. Note that *config* or *external* can be NULL (but not both NULL).

## Remarks

*external* either points to a structure of type **MEIEventMgrConfig{}** or is NULL.

### Return Values

[MPIMessageOK](#)

## See Also

[mpiEventMgrConfigGet](#)

# mpiEventMgrEvent

## Declaration

```
long mpiEventMgrEvent( MPIEventMgr    eventMgr ,  
                      MPIEventStatus *status )
```

**Required Header:** stdmpi.h

## Description

**mpiEventMgrEvent** requests that the EventMgr (*eventMgr*) call mpiNotifyEvent(notify, status) for all Notify objects on that Event Manager's list. Each Notify object represents a thread that has requested event notification. The Notify object will determine whether it accepts the event notification or not.

EventMgrEvent enables your application to use the Event Manager to distribute *user-created events* in the same way that events generated by the motion controller are distributed.

### Return Values

[MPIMessageOK](#)

## See Also

# meiEventMgrServiceConfigGet

## Declaration

```
long meiEventMgrServiceConfigGet(MPIEventMgr eventMgr,  
                                MEIEventMgrServiceConfig *config)
```

Required Header: stdmpi.h

## Description

**meiEventMgrServiceConfigGet** gets the configuration of an *EventMgr* object (`eventMgr`) and writes it into the structure pointed to by *config*.

## Return Values

[MPIMessageOK](#)

## See Also

[meiEventMgrServiceConfigSet](#) | [mpiEventMgrService](#)

# meiEventMgrServiceConfigSet

## Declaration

```
long meiEventMgrServiceConfigGet(MPIEventMgr eventMgr,  
                                 MEIEventMgrServiceConfig *config)
```

Required Header: stdmpi.h

## Description

**meiEventMgrServiceConfigSet** sets (writes) the flash configuration for an EventMgr object (*eventMgr*) using data from the structure pointed to by *config*.

### Return Values

[MPIMessageOK](#)

## See Also

[meiEventMgrServiceConfigGet](#) | [mpiEventMgrService](#)

# mpiEventMgrFlush

## Declaration

```
long mpiEventMgrFlush(MPIEventMgr eventMgr )
```

Required Header: stdmpi.h

## Description

**mpiEventMgrFlush** flushes any pending events from an EventMgr (*eventMgr*).

### Return Values

[MPIMessageOK](#)

## See Also

# mpiEventMgrControl

## Declaration

```
MPIControl mpiEventMgrControl(MPIEventMgr eventMgr,
                               long index)
```

Required Header: stdmpi.h

## Description

**mpiEventMgrControl** returns the element at the position on the list indicated by *index*.

<b>eventMgr</b>	a handle to the EventMgr object.
<b>index</b>	a position in the list.

### Return Values

<a href="#">MPIMessageOK</a>	
<b>handle</b>	to the <i>index</i> th motion controller (Control) associated with an EventMgr ( <i>eventMgr</i> )
<b>MPIHandleVOID</b>	if <i>eventMgr</i> is invalid if <i>index</i> is less than 0 if <i>index</i> is greater than or equal to <b>mpiEventMgrCount(eventMgr)</b>
<a href="#">MPIMessageARG_INVALID</a>	
<a href="#">MEIListMessageELEMENT_NOT_FOUND</a>	
<a href="#">MPIMessageHANDLE_INVALID</a>	

## See Also

# mpiEventMgrControlAppend

## Declaration

```
long mpiEventMgrControlAppend(MPIEventMgr eventMgr,  
                               MPIControl control)
```

**Required Header:** stdmpi.h

## Description

**mpiEventMgrControlAppend** appends *control* to the list of motion controllers associated with an EventMgr (*eventMgr*). Add "control" to the end of the list.

<b>eventMgr</b>	a handle to the EventMgr object.
<b>control</b>	a handle to a Control object.

## Return Values

[MPIMessageOK](#)

[MPIMessageHANDLE\\_INVALID](#)

[MPIMessageOBJECT\\_ON\\_LIST](#)

[MPIMessageNO\\_MEMORY](#)

## See Also

# mpiEventMgrControlCount

## Declaration

```
long mpiEventMgrControlCount( MPIEventMgr eventMgr )
```

**Required Header:** stdmpi.h

## Description

**mpiEventMgrControlCount** returns the number of elements on the list.

<b>eventMgr</b>	a handle to the EventMgr object.
-----------------	----------------------------------

### Return Values

<b>number</b>	of motion controllers associated with an EventMgr ( <i>eventMgr</i> )
---------------	---

<b>-1</b>	if <i>eventMgr</i> is an invalid handle
-----------	---

<b>0</b>	if <i>eventMgr</i> has no associated motion controllers
----------	---

## See Also



# mpiEventMgrControlFirst

## Declaration

```
MPIControl mpiEventMgrControlFirst(MPIEventMgr eventMgr)
```

**Required Header:** stdmpi.h

## Description

**mpiEventMgrControlFirst** returns the first element in the list. This function can be used in conjunction with [mpiEventMgrControlNext\(...\)](#) in order to iterate through the list. MPIHandleVOID is returned if the list is empty.

<b>eventMgr</b>	a handle to the EventMgr object.
-----------------	----------------------------------

### Return Values

<b>handle</b>	to the first motion controller (Control) associated with an EventMgr ( <i>eventMgr</i> )
<b>MPIHandleVOID</b>	if <i>eventMgr</i> is invalid if <i>eventMgr</i> has no associated motion controllers
<a href="#">MPIMessageHANDLE_INVALID</a>	

## See Also

[mpiEventMgrControlLast](#)

# mpiEventMgrControlIndex

## Declaration

```
long mpiEventMgrControlIndex(MPIEventMgr eventMgr ,
                             MPIControl control )
```

Required Header: stdmpi.h

## Description

**mpiEventMgrControlIndex** returns the position of "control" on the list.

<b>eventMgr</b>	a handle to the EventMgr object.
<b>control</b>	a handle to a Control object.

### Return Values

<b>index</b>	of <b>control</b> in the list of motion controllers associated with an EventMgr ( <b>eventMgr</b> )
<b>-1</b>	if <b>eventMgr</b> is invalid if <b>control</b> was not found in the list of motion controllers

## See Also

# mpiEventMgrControlInsert

## Declaration

```
long mpiEventMgrControlInsert (MPIEventMgr eventMgr ,
                               MPIControl  control ,
                               MPIControl  insert )
```

Required Header: stdmpi.h

## Description

**mpiEventMgrControlInsert** inserts a Control object (*insert*) after the Control object (*control*) in the list of motion controllers associated with *eventMgr*.

<b>eventMgr</b>	a handle to the EventMgr object.
-----------------	----------------------------------

### Return Values

<b>MPIMessageOK</b>	if <i>EventMgrControlInsert</i> successfully inserts the Control object ( <i>insert</i> ) after another Control object ( <i>control</i> ) in the list of motion controllers
---------------------	---

## See Also

# mpiEventMgrControlLast

## Declaration

```
MPIControl mpiEventMgrControlLast(MPIEventMgr eventMgr)
```

Required Header: stdmpi.h

## Description

**mpiEventMgrControlLast** returns the last element in the list.

This function can be used in conjunction with `mpiEventMgrControlPrevious()` in order to iterate through the list backwards.

<b>eventMgr</b>	a handle to the EventMgr object.
-----------------	----------------------------------

### Return Values

<b>handle</b>	to the last motion controller (Control) associated with an EventMgr ( <i>eventMgr</i> )
<b>MPIHandleVOID</b>	if <i>eventMgr</i> is invalid if <i>eventMgr</i> has no associated motion controllers
<a href="#">MPIMessageHANDLE_INVALID</a>	

## See Also

[mpiEventMgrControlFirst](#)

# mpiEventMgrControlListGet

## Declaration

```
long mpiEventMgrControlListGet(MPIEventMgr eventMgr ,  
                                long *controlCount ,  
                                MPIControl *controlList )
```

Required Header: stdmpi.h

## Description

**mpiEventMgrControlListGet** returns the list of Control objects associated with an EventMgr object (*eventMgr*).

**EventMgrControlListGet** also writes the number of Control handles (in the list) to the location pointed to by *controlCount*, and writes an array (of *controlCount* Control handles) to the location pointed to by *controlList*.

<b>eventMgr</b>	a handle to the EventMgr object.
-----------------	----------------------------------

## Return Values

[MPIMessageOK](#)

## See Also

[mpiEventMgrControlListSet](#)

# mpiEventMgrControlListSet

## Declaration

```
long mpiEventMgrControlListSet(MPIEventMgr eventMgr ,  
                                long          controlCount ,  
                                MPIControl   *controlList )
```

Required Header: stdmpi.h

## Description

**mpiEventMgrControlListSet** creates a list of **controlCount** Control objects using the Control handles specified by **controlList**. Any existing motion controller list is completely replaced.

The **controlList** parameter is the address of an array of **controlCount** Control handles, or is NULL (if **controlCount** is equal to zero).

A motion controller list can also be created incrementally (i.e., one Control at a time) by using the append and/or insert methods described in this section. The initial Control of a control list may be specified using the **control** parameter of [mpiEventMgrCreate\(...\)](#). The list methods in this section can be used to examine and manipulate a motion controller list regardless of how the list was created.

## Return Values

[MPIMessageOK](#)

## See Also

[mpiEventMgrControlListGet](#)

# mpiEventMgrControlNext

## Declaration

```
MPIControl mpiEventMgrControlNext(MPIEventMgr eventMgr ,  
                                  MPIControl control )
```

**Required Header:** stdmpi.h

## Description

**mpiEventMgrControlNext** returns the next element following "control" on the list. MPIHandleVOID is returned if "control" is the last element on the list, or if "control" is not in the list at all. This function can be used in conjunction with mpiEventMgrControlFirst() in order to iterate through the list.

<b>eventMgr</b>	a handle to the EventMgr object.
<b>control</b>	a handle to a Control object.

Return Values	
<b>handle</b>	to the motion controller following <b>control</b> in the list of motion controllers associated with an EventMgr ( <b>eventMgr</b> )
<b>MPIHandleVOID</b>	if <b>eventMgr</b> is invalid if <b>control</b> is the last motion controller
<a href="#">MPIMessageHANDLE_INVALID</a>	

## See Also

[mpiEventMgrControlPrevious](#)

# mpiEventMgrControlPrevious

## Declaration

```
MPIControl mpiEventMgrControlPrevious(MPIEventMgr eventMgr ,  
                                     MPIControl control )
```

Required Header: stdmpi.h

## Description

**mpiEventMgrControlPrevious** returns the previous element prior to "control" on the list. MPIHandleVOID is returned if "control" is the first element on the list, or if "control" is not in the list at all. This function can be used in conjunction with [mpiEventMgrControlLast\(...\)](#) in order to iterate through the list backwards.

<b>eventMgr</b>	a handle to the EventMgr object.
<b>control</b>	a handle to a Control object.

## Return Values

<b>handle</b>	to the motion controller preceding <b>control</b> in the list of motion controllers associated with an EventMgr ( <b>eventMgr</b> )
<b>MPIHandleVOID</b>	if <b>eventMgr</b> is invalid if <b>control</b> is the first motion controller
<a href="#">MPIMessageHANDLE_INVALID</a>	

## See Also

[mpiEventMgrControlNext](#)



# mpiEventMgrControlRemove

## Declaration

```
long mpiEventMgrControlRemove(MPIEventMgr eventMgr,  
                               MPIControl control)
```

Required Header: stdmpi.h

## Description

**mpiEventMgrControlRemove** removes a Control object (*control*) from the list of Control objects associated with *eventMgr*.

<b>eventMgr</b>	a handle to the EventMgr object.
<b>control</b>	a handle to a Control object.

## Return Values

### MPIMessageOK

if *EventMgrControlRemove* successfully removes a Control object from the list of Control objects associated with an EventMgr (*eventMgr*)

## See Also

[mpiEventMgrControl](#)

# mpiEventMgrNotify

## Declaration

```
MPINotify mpiEventMgrNotify(MPIEventMgr eventMgr ,
                             long          index )
```

Required Header: stdmpi.h

## Description

**mpiEventMgrNotify** returns the element at the position on the list indicated by *index*.

<b>eventMgr</b>	a handle to the EventMgr object.
<b>index</b>	a position in the list.

## Return Values

<b>handle</b>	to the <i>index</i> th Notify object associated with an EventMgr ( <i>eventMgr</i> )
<b>MPIHandleVOID</b>	if <i>eventMgr</i> is invalid if <i>index</i> is less than 0 if <i>index</i> is greater than or equal to <b>mpiEventMgrCount(eventMgr)</b>
<a href="#">MPIMessageARG_INVALID</a>	
<a href="#">MEIListMessageELEMENT_NOT_FOUND</a>	
<a href="#">MPIMessageHANDLE_INVALID</a>	

## See Also

# mpiEventMgrNotifyAppend

## Declaration

```
long mpiEventMgrNotifyAppend(MPIEventMgr eventMgr ,
                             MPINotify notify)
```

**Required Header:** stdmpi.h

## Description

**mpiEventMgrNotifyAppend** appends a Notify object (*notify*) to the list of Notify objects maintained by an EventMgr object (*eventMgr*).

<b>eventMgr</b>	a handle to the EventMgr object.
<b>notify</b>	a handle to a Notify object.

### Return Values

[MPIMessageOK](#)

[MPIMessageHANDLE\\_INVALID](#)

[MPIMessageOBJECT\\_ON\\_LIST](#)

[MPIMessageNO\\_MEMORY](#)

## See Also

# mpiEventMgrNotifyCount

## Declaration

```
long mpiEventMgrNotifyCount (MPIEventMgr eventMgr )
```

Required Header: stdmpi.h

## Description

**mpiEventMgrNotifyCount** returns the number of elements on the list.

<b>eventMgr</b>	a handle to the EventMgr object.
-----------------	----------------------------------

### Return Values

<b>number</b>	of Notify objects in the list (of Notify objects) maintained by an EventMgr ( <i>eventMgr</i> )
<b>-1</b>	if <i>eventMgr</i> is invalid
<b>0</b>	if the list (of Notify objects) is empty

## See Also

# mpiEventMgrNotifyFirst

## Declaration

```
MPINotify mpiEventMgrNotifyFirst(MPIEventMgr eventMgr)
```

Required Header: stdmpi.h

## Description

**mpiEventMgrNotifyFirst** returns the first element in the list. This function can be used in conjunction with [mpiEventMgrNotifyNext\(...\)](#) in order to iterate through the list.

<b>eventMgr</b>	a handle to the EventMgr object.
-----------------	----------------------------------

### Return Values

<b>handle</b>	to the first Notify object in the list (of Notify objects) maintained by an EventMgr ( <b>eventMgr</b> )
<b>MPIHandleVOID</b>	if <b>eventMgr</b> is invalid if the list (of Notify objects) is empty
<a href="#">MPIMessageHANDLE_INVALID</a>	

## See Also

[mpiEventMgrNotifyLast](#) | [mpiEventMgrNotifyNext](#)

# mpiEventMgrNotifyIndex

## Declaration

```
long mpiEventMgrNotifyIndex(MPIEventMgr eventMgr ,
                            MPINotify notify)
```

Required Header: stdmpi.h

## Description

**mpiEventMgrNotifyIndex** returns the position of *notify* on the list.

<b>eventMgr</b>	a handle to the EventMgr object.
<b>notify</b>	a handle to the EventMgr object.

### Return Values

<b>index</b>	of <i>notify</i> in the list (of Notify objects) maintained by an EventMgr ( <i>eventMgr</i> )
<b>-1</b>	if eventMgr is invalid if <i>notify</i> was not found in the list

## See Also

# mpiEventMgrNotifyInsert

## Declaration

```
long mpiEventMgrNotifyInsert (MPIEventMgr eventMgr ,  
                              MPINotify   notify ,  
                              MPINotify   insert )
```

Required Header: stdmpi.h

## Description

**mpiEventMgrNotifyInsert** places a Notify object (*insert*) after another Notify object (*notify*) in the list (of Notify objects) maintained by an EventMgr object (*eventMgr*).

### Return Values

[MPIMessageOK](#)

## See Also

# mpiEventMgrNotifyLast

## Declaration

```
MPINotify mpiEventMgrNotifyLast(MPIEventMgr eventMgr )
```

**Required Header:** stdmpi.h

## Description

**mpiEventMgrNotifyLast** returns the last element in the list. This function can be used in conjunction with [mpiEventMgrNotifyPrevious\(...\)](#) in order to iterate through the list backwards.

<b>eventMgr</b>	a handle to the EventMgr object.
-----------------	----------------------------------

### Return Values

<b>handle</b>	to the first Notify object in the list (of Notify objects) maintained by an EventMgr ( <b>eventMgr</b> )
---------------	--

<b>MPIHandleVOID</b>	if <b>eventMgr</b> is invalid if the list (of Notify objects) is empty
----------------------	---

<a href="#">MPIMessageHANDLE_INVALID</a>	
--	--

## See Also

[mpiEventMgrNotifyFirst](#) | [mpiEventMgrNotifyPrevious](#)



# mpiEventMgrNotifyListGet

## Declaration

```
long mpiEventMgrNotifyListGet(MPIEventMgr eventMgr,  
                              long          *notifyCount,  
                              MPINotify   *notifyList)
```

Required Header: stdmpi.h

## Description

**mpiEventMgrNotifyListGet** returns the list of Notify objects for an EventMgr object (*eventMgr*). *EventMgrNotifyListGet* also sets (writes) the number (of Notify objects in the list) to the location pointed to by *notifyCount*, and sets (writes) an array (of *notifyCount* Notify handles) to the contents of the location pointed to by *notifyList*.

## Return Values

[MPIMessageOK](#)

## See Also

[mpiEventMgrNotifyListSet](#)

# mpiEventMgrNotifyListSet

## Declaration

```
long mpiEventMgrNotifyListSet(MPIEventMgr eventMgr ,
                               long          notifyCount ,
                               MPINotify   *notifyList )
```

**Required Header:** stdmpi.h

## Description

**mpiEventMgrNotifyListSet** creates a list of Notify objects, where the number of Notify objects is specified by **notifyCount**, using the Notify handles specified by **notifyList**. The **notifyList** argument is the address of an array of **notifyCount** Notify handles, or is NULL if **notifyCount** is zero. Any existing notify object list is completely replaced.

You can also create a Notify object list incrementally (i.e., one Notify object is created at a time), by using the EventMgrAppend and/or EventMgrInsert methods. After creating a list of Notify objects, use the EventMgrList methods to examine and manipulate the list, regardless of how the list was created.

## Return Values

[MPIMessageOK](#)

## See Also

[mpiEventMgrNotifyListGet](#)

# mpiEventMgrNotifyNext

## Declaration

```
MPINotify mpiEventMgrNotifyNext(MPIEventMgr eventMgr ,
                                MPINotify notify)
```

Required Header: stdmpi.h

## Description

**mpiEventMgrNotifyNext** returns the next element following *notify* on the list. This function can be used in conjunction with [mpiEventMgrNotifyFirst\(...\)](#) in order to iterate through the list.

<b>eventMgr</b>	a handle to the EventMgr object.
<b>notify</b>	a handle to a Notify object.

Return Values	
<b>handle</b>	to the first Notify object in the list (of Notify objects) maintained by an EventMgr ( <i>eventMgr</i> )
<b>MPIHandleVOID</b>	if <i>eventMgr</i> is invalid if the list (of Notify objects) is empty
<a href="#">MPIMessageHANDLE_INVALID</a>	

## See Also

[mpiEventMgrNotifyPrevious](#) | [mpiEventMgrNotifyFirst](#)

# mpiEventMgrNotifyPrevious

## Declaration

```
MPINotify mpiEventMgrNotifyPrevious( MPIEventMgr eventMgr ,
                                     MPINotify   notify )
```

Required Header: stdmpi.h

## Description

**mpiEventMgrNotifyPrevious** returns the previous element prior to **notify** on the list. This function can be used in conjunction with `mpiEventMgrNotifyLast(...)` in order to iterate through the list backwards.

<b>eventMgr</b>	a handle to the EventMgr object.
<b>notify</b>	a handle to a Notify object.

Return Values	
<b>handle</b>	to the Notify object just before another Notify object ( <b>notify</b> ) in the list (of Notify objects) maintained by an EventMgr ( <b>eventMgr</b> )
<b>MPIHandleVOID</b>	if <b>eventMgr</b> is invalid if <b>notify</b> is the first Notify object in the list
<b>MPIMessageHANDLE_INVALID</b>	either <b>eventMgr</b> or <b>notify</b> is an invalid handle

## See Also

[mpiEventMgrNotifyNext](#) | [mpiEventMgrNotifyLast](#)

# mpiEventMgrNotifyRemove

## Declaration

```
long mpiEventMgrNotifyRemove(MPIEventMgr eventMgr ,  
                             MPINotify notify)
```

**Required Header:** stdmpi.h

## Description

**mpiEventMgrNotifyRemove** removes a Notify object (*notify*) from the list of Notify objects maintained by an EventMgr object (*eventMgr*).

<b>eventMgr</b>	a handle to the EventMgr object.
<b>notify</b>	a handle to a Notify object.

## Return Values

[MPIMessageOK](#)

## See Also

# MPIEventMgrConfig

## Definition

```
typedef MPIEmpty MPIEventMgrConfig;
```

**Change History:** Modified in the 03.03.00

## Description

**MPIEventMgrConfig** is an empty structure. It is a placeholder for possible future EventMgr configurations.

## See Also

# MPIEventMgrMessage

## Definition

```
typedef enum {  
  
    MPIEventMgrMessageEVENTMGR_INVALID,  
} MPIEventMgrMessage;
```

## Description

**MPIEventMessage** is an enumeration of the EventMgr error messages that can be returned by the MPI library.

### MPIEventMgrMessageEVENTMGR\_INVALID

Not supported.

## Sample Code

```
MPIControl      control;  
MPIEventMgr     eventMgr;  
long            returnValue;  
.  
  
eventMgr =  
    mpiEventMgrCreate(control);  
returnValue =  
    mpiEventMgrValidate(eventMgr);
```

## See Also

[MPIEventMgr](#) | [mpiEventMgrCreate](#) | [mpiEventMgrValidate](#)

# MEIEventMgrServiceConfig

## Definition

```
typedef struct MEIEventMgrServiceConfig {  
    MPI_BOOL  allProcesses; /* TRUE => collect  
                               events from all processes,  
                               else EventMgr process only */  
} MEIEventMgrServiceConfig;
```

**Change History:** Modified in the 03.03.00

## Description

### **allProcesses**

is a boolean value. If allProcesses=TRUE, then the event manager will handle events originating from all processes. If allProcesses=FALSE, then the event manager will only handle events originating from the same process in which the event manager was created.

## See Also